



J & K POLICE

+

SRINAGAR

POLICE CONTROL ROOM COMPLEX, BATAMALOO, SRINAGAR - 190009


+91-194-2479915

msphsgr@jkpolice.gov.in

NIT Order No. 78 OF 2017
DATED 10.10.2017.

For and on behalf of Government of Jammu & Kashmir, Medical Superintendent, JK Police Hospital Srinagar invites sealed tenders from eligible and qualified bidders for supply of Audio/ Video equipments to this hospital. The tenders should be affixed with revenue stamp of Rs.06/= and accompanied with CDR/FDR worth Rs.3,000/= (rupees three thousand only) pledged to Medical Superintendent, JK Police Hospital Srinagar.

The tender documents, together with details and terms & condition can be had from the office of the undersigned on any working day till 31.10.2017. These will be opened on 01.11.2017 in presence of bidders who may like to be present at that time. However, in case of holiday/unforeseen circumstances tenders will be opened on the next working day.


Medical Superintendent.
JK Police Hospital, Srinagar.

No: PHS/Accts/Tenders/2017 / 4776-78
Dated:- 10.10.2017

Copy to:

1. Joint Director Information, Srinagar with the request that the NIT may please be given wide publicity through local dailies.
2. I/C Purchase Committee, JK Police Hospital Srinagar
3. I/C Accounts Branch, JK Police Hospital Srinagar
..... for information and necessary action.

**SPECIFICATION OF AUDIO VIDEO EQUIPMENT REQUIRED FOR LIVE SURGICAL
WORKSHOPS IN THE AUDITORIUM OF POLICE HOSPITAL SRINAGAR**

⇒ VIDEO SWITCHER: 01 Unit.

- Picture in picture
- Built in effects
- 4 BNC composite video
- 1 RCA unbalanced stereo audio.
2X1/4" 0.6 mm
- Video band width: Component 5.2 MHZ
S-Video y/c 5.0 HM
3 BNC Component Video Output.

⇒ MULTI VIDEO CONVERTORS: 01 Unit

- Maximum data Rate 6.756 GHz
- Maximum Pixels: 225 MHz.
- Video: Composite video.
- Band width: 300 MHz.
- Video Input:
 - VGA - 2 VGA – QxGA
 - DVI Input - 2 Single line DVI-D
 - HDMI Input - 3 HDMI Inputs.
 - Composite Input - 2 NTSC/ PAL
- Video Output:
 - VGA Output - 1 VGA output.
 - HDMI Output: - 1 HDMI
 - Composite Video: - 1 out put of Composite.
- DVI to VGA
- DVI to A/V
- SDI to A/V

⇒ FULL HD CAMERAS: 02 Units

- 1/3.1 Inch Sensor.
- Built in LED Video Light.
- 2 Filters Included.
- 20x Optical Zoom.
- Dual SD Card Slot.
- Low Light Video.
- 3 Manual Rings.
- 2 Channel XLR Terminals.

- ⇒ **TRIPODS FOR CAMERAS:** **02 Units**
- Load Capacity: 7500 grams.
 - Height Range: 690 mm – 1500 mm
 - No. of Legs: 03 No.s
 - Material: Aluminum.
- ⇒ **MEDIA CONVERTOR:** **02 SETS.**
- ⇒ Digital convertor
- Transmission Distance: 550 M – 40/80 KM
 - Wave length: 1310/ 1550 mm.
 - 10-Bit Digital code and non compression type video transmission.
 - Compatible Video system: PAL/ SeCAM/ NTSC.
- ⇒ **WIRELESS MIKES (LAPEL)** **02 No.s**
- UHF Cordless Mike: 460-970 Mhz.
 - Polar Pattern: Cardioid
 - Frequency Response: 50 Hz – 15 KHz.
 - Output: Balanced x LR/ Unbalanced ¼” Jack.
 - Receiver: 240 A/C 50 Hz for A/C Adaptor.
- ⇒ **CORDLESS MIKES (HANDHELD)** **01 Unit**
- Dual Mikes: Non Diversity.
 - Frequency Response: 50 Hz – 16 KHz.
 - Output: Individual Channel x LR/ Mix Out ¼” Jack.
 - Receiver: 240 A/C 50 Hz for A/C.
 - Polar Pattern: Cardioid
- ⇒ **AUDIO CONSOLE:** **01 Unit**
- Built in SPX Digital Effect.
 - Bi-Directional USB, One knob compressor.
 - D-Pre Mic Preamps with an inverted Darlington circuit.
- ⇒ **VIDEO CABLING:**
- High sensitive cable: 300 meters
 - HDMI cable: 20 meters.
 - VGA cable: 5 meters.

⇒ **PROGRAMME RECORDERS:** **01 Unit.**

- Recording the programmes in HD Format.
- USB port: In/ Out.
- HDMI: In/ Out with 1080i/ 720p
- yRBP: yRBP In/Out

⇒ **MONITORS:** **02 No.s**

- 9" LED Monitors.
- 9" Field Monitors with HDMI -In/ Out
- AV In-Out.
- Color Bar/ Colour Adjustment.
- Screen Marker.
- Panel size: 9" TFT LCD (16:9)
- Input Voltage: DC 6 -24V.

⇒ **POWERED SPEAKERS** **02 No.s**